

## SAFETY DATA SHEET

### Section 1. Identification

**Product identifier** : 712A  
**Product name** : 1K Sprayout Clearcoat  
**Date of issue** : 2/12/2024  
**Version** : 18

#### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** : Coating component.  
**Uses advised against** : Not for sale to or use by consumers.

**Supplier's details** : Axalta Coating Systems Canada Company  
1915 2nd St. W  
Cornwall, ON K6H5R6

**Product information** : 613-932-8960


**Emergency telephone number** : (CHEMTREC) - 800-424-9300

### Section 2. Hazard identification

**Classification of the substance or mixture** : FLAMMABLE AEROSOLS - Category 1  
GASES UNDER PRESSURE - Compressed gas  
EYE IRRITATION - Category 2A  
SKIN SENSITIZATION - Category 1A  
CARCINOGENICITY - Category 2  
TOXIC TO REPRODUCTION - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3

#### GHS label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : H222 - Extremely flammable aerosol.  
H280 - Contains gas under pressure; may explode if heated.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H351 - Suspected of causing cancer.  
H361 - Suspected of damaging fertility or the unborn child.

#### Precautionary statements

## Section 2. Hazard identification

|                                    |  |
|------------------------------------|--|
| <b>Prevention</b>                  | : P201 - Obtain special instructions before use.<br>P202 - Do not handle until all safety precautions have been read and understood.<br>P280 - Wear protective gloves, protective clothing and eye or face protection.<br>P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>P211 - Do not spray on an open flame or other ignition source.<br>P271 - Use only outdoors or in a well-ventilated area.<br>P261 - Avoid breathing dust or mist.<br>P264 - Wash hands thoroughly after handling.<br>P272 - Contaminated work clothing should not be allowed out of the workplace.<br>P251 - Do not pierce or burn, even after use.        |
| <b>Response</b>                    | : P308 + P313 - IF exposed or concerned: Get medical advice or attention.<br>P304 + P340, P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.<br>P362 + P364 - Take off contaminated clothing and wash it before reuse.<br>P302 + P352 - IF ON SKIN: Wash with plenty of water.<br>P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.<br>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.<br>P337 + P313 - If eye irritation persists: Get medical advice or attention. |
| <b>Storage</b>                     | : P405 - Store locked up.<br>P410 + P403 - Protect from sunlight.<br>P410 + P412 - Do not expose to temperatures exceeding 50 °C/122 °F.<br>P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.   |
| <b>Disposal</b>                    | : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.   |
| <b>Supplemental label elements</b> | : None known.  |

**Other hazards which do not result in classification** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

| Chemical name                   | Common name and Synonyms          | CAS number | % (w/w)   |
|---------------------------------|-----------------------------------|------------|-----------|
| n-butyl acetate                 | BUTYL ACETATE                     | 123-86-4   | ≥10 - ≤30 |
| acetone                         | ACETONE                           | 67-64-1    | ≥10 - ≤30 |
| propane                         | PROPANE                           | 74-98-6    | ≥10 - ≤30 |
| Isopropyl alcohol               | ISOPROPYL ALCOHOL                 | 67-63-0    | ≥5 - ≤10  |
| Isobutane                       | ISOBUTAN                          | 75-28-5    | ≥5 - ≤10  |
| butane                          | BUTANE                            | 106-97-8   | ≥5 - ≤10  |
| ethyl acetate                   | ETHYL ACETATE                     | 141-78-6   | ≥1 - ≤5   |
| XYLENE                          | XYLENE                            | 1330-20-7  | ≥1 - ≤5   |
| 2-methoxy-1-methylethyl acetate | PROPYLENE GLYCOL MONOMETHYL ETHER | 108-65-6   | ≥1 - ≤5   |

### Section 3. Composition/information on ingredients

|   |   |             |           |
|---|---|-------------|-----------|
|   | ACETATE   |             |           |
| ethylbenzene  | ETHYLBENZENE  | 100-41-4    | ≥0.1 - ≤1 |
| BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATE   | BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATE   | 41556-26-7  | ≥0.1 - ≤1 |
| Poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-ω-hydroxy- | POLY(OXY-1,2-ETHANEDIYL),. ALPHA.-[3-[3-(2H-BENZOTRIAZOL-2-YL)-5-(1,1-DIMETHYLETHYL)-4-HYDROXY PHENYL | 104810-48-2 | ≥0.1 - ≤1 |
| ULTRAVIOLET ABSORBER  | ULTRAVIOLET ABSORBER  | 104810-47-1 | ≥0.1 - ≤1 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

**Occupational exposure limits, if available, are listed in Section 8.**

### Section 4. First-aid measures

#### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### Most important symptoms/effects, acute and delayed

##### Potential acute health effects

- Eye contact** : Causes serious eye irritation.

## Section 4. First-aid measures

- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
nausea or vomiting  
headache  
drowsiness/fatigue  
dizziness/vertigo  
unconsciousness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

## Section 5. Fire-fighting measures

- Specific hazards arising from the chemical** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.
- Storage code** : IB

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name | Exposure limits   |
|-----------------|---|
| n-butyl acetate | <p><b>CA Alberta Provincial (Canada, 6/2018).</b><br/>           OEL: 200 ppm 15 minutes.<br/>           OEL: 950 mg/m<sup>3</sup> 15 minutes.<br/>           OEL: 150 ppm 8 hours.<br/>           OEL: 713 mg/m<sup>3</sup> 8 hours.</p> <p><b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br/>           STEL: 200 ppm 15 minutes.<br/>           TWA: 150 ppm 8 hours.</p> <p><b>CA Ontario Provincial (Canada, 6/2019). [butyl acetates, all isomers]</b><br/>           STEL: 150 ppm 15 minutes.<br/>           TWA: 50 ppm 8 hours.</p> <p><b>CA British Columbia Provincial (Canada, 6/2023). [butyl acetate, all isomers]</b><br/>           STEL: 150 ppm 15 minutes.<br/>           TWA: 50 ppm 8 hours.</p> <p><b>CA Quebec Provincial (Canada, 6/2022). [butyl acetates]</b><br/>           STEV: 150 ppm 15 minutes.<br/>           TWAEV: 50 ppm 8 hours.</p> |
| acetone         | <p><b>CA Alberta Provincial (Canada, 6/2018).</b></p>   |

## Section 8. Exposure controls/personal protection

|                   |  |
|-------------------|--|
| propane           | <p>OEL: 1200 mg/m<sup>3</sup> 8 hours.<br/> OEL: 1800 mg/m<sup>3</sup> 15 minutes.<br/> OEL: 500 ppm 8 hours.<br/> OEL: 750 ppm 15 minutes.<br/> <b>CA British Columbia Provincial (Canada, 6/2023).</b><br/> TWA: 250 ppm 8 hours.<br/> STEL: 500 ppm 15 minutes.<br/> <b>CA Ontario Provincial (Canada, 6/2019).</b><br/> TWA: 250 ppm 8 hours.<br/> STEL: 500 ppm 15 minutes.<br/> <b>CA Quebec Provincial (Canada, 6/2022).</b><br/> TWAEV: 250 ppm 8 hours.<br/> STEV: 500 ppm 15 minutes.<br/> <b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br/> STEL: 750 ppm 15 minutes.<br/> TWA: 500 ppm 8 hours.</p> <p><b>CA Alberta Provincial (Canada, 6/2018).</b><br/> OEL: 1000 ppm 8 hours.<br/> <b>CA Quebec Provincial (Canada, 6/2022).</b><br/> TWAEV: 1000 ppm 8 hours.<br/> TWAEV: 1800 mg/m<sup>3</sup> 8 hours.<br/> <b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br/> STEL: 1250 ppm 15 minutes.<br/> TWA: 1000 ppm 8 hours.<br/> <b>CA British Columbia Provincial (Canada, 6/2023).</b><br/> <b>Oxygen Depletion [Asphyxiant]. Explosive potential.</b></p> |
| Isopropyl alcohol | <p><b>CA Ontario Provincial (Canada, 6/2019).</b> <b>Oxygen Depletion [Asphyxiant]. Explosive potential.</b></p> <p><b>CA Alberta Provincial (Canada, 6/2018).</b><br/> OEL: 984 mg/m<sup>3</sup> 15 minutes.<br/> OEL: 200 ppm 8 hours.<br/> OEL: 400 ppm 15 minutes.<br/> OEL: 492 mg/m<sup>3</sup> 8 hours.<br/> <b>CA British Columbia Provincial (Canada, 6/2023).</b><br/> TWA: 200 ppm 8 hours.<br/> STEL: 400 ppm 15 minutes.<br/> <b>CA Ontario Provincial (Canada, 6/2019).</b><br/> TWA: 200 ppm 8 hours.<br/> STEL: 400 ppm 15 minutes.<br/> <b>CA Quebec Provincial (Canada, 6/2022).</b><br/> TWAEV: 200 ppm 8 hours.<br/> STEV: 400 ppm 15 minutes.<br/> <b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br/> STEL: 400 ppm 15 minutes.<br/> TWA: 200 ppm 8 hours.</p>  |
| Isobutane         | <p><b>CA Alberta Provincial (Canada, 6/2018).</b> <b>[Aliphatic Hydrocarbon gases, Alkane (C2-C4)]</b><br/> OEL: 1000 ppm 8 hours.<br/> <b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br/> <b>[Butane]</b><br/> STEL: 1250 ppm 15 minutes.<br/> TWA: 1000 ppm 8 hours.<br/> <b>CA Ontario Provincial (Canada, 6/2019).</b> <b>[Butane, All isomers] Explosive potential.</b></p>   |

**Section 8. Exposure controls/personal protection**

|                      |   |
|----------------------|---|
| <p>butane</p>        | <p>STEL: 1000 ppm 15 minutes.<br/> <b>CA British Columbia Provincial (Canada, 6/2023).</b><br/> <b>[butane, all isomers] Explosive potential.</b><br/>                 STEL: 1000 ppm 15 minutes.<br/> <b>CA Alberta Provincial (Canada, 6/2018).</b><br/>                 OEL: 1000 ppm 8 hours.<br/> <b>CA Quebec Provincial (Canada, 6/2022).</b><br/>                 TWAEV: 800 ppm 8 hours.<br/>                 TWAEV: 1900 mg/m<sup>3</sup> 8 hours.<br/> <b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br/> <b>[Butane]</b><br/>                 STEL: 1250 ppm 15 minutes.<br/>                 TWA: 1000 ppm 8 hours.<br/> <b>CA Ontario Provincial (Canada, 6/2019).</b> <b>[Butane, All isomers] Explosive potential.</b><br/>                 STEL: 1000 ppm 15 minutes.<br/> <b>CA British Columbia Provincial (Canada, 6/2023).</b><br/> <b>[butane, all isomers] Explosive potential.</b><br/>                 STEL: 1000 ppm 15 minutes.</p>  |
| <p>ethyl acetate</p> | <p><b>CA Alberta Provincial (Canada, 6/2018).</b><br/>                 OEL: 1440 mg/m<sup>3</sup> 8 hours.<br/>                 OEL: 400 ppm 8 hours.<br/> <b>CA British Columbia Provincial (Canada, 6/2023).</b><br/>                 TWA: 150 ppm 8 hours.<br/> <b>CA Ontario Provincial (Canada, 6/2019).</b><br/>                 TWA: 400 ppm 8 hours.<br/> <b>CA Quebec Provincial (Canada, 6/2022).</b><br/>                 TWAEV: 400 ppm 8 hours.<br/>                 TWAEV: 1440 mg/m<sup>3</sup> 8 hours.<br/> <b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br/>                 STEL: 500 ppm 15 minutes.<br/>                 TWA: 400 ppm 8 hours.</p>  |
| <p>XYLENE</p>        | <p><b>CA Alberta Provincial (Canada, 6/2018).</b><br/> <b>[Dimethylbenzene]</b><br/>                 OEL: 100 ppm 8 hours.<br/>                 OEL: 651 mg/m<sup>3</sup> 15 minutes.<br/>                 OEL: 150 ppm 15 minutes.<br/>                 OEL: 434 mg/m<sup>3</sup> 8 hours.<br/> <b>CA British Columbia Provincial (Canada, 6/2023).</b><br/> <b>[Xylene (o, m &amp; p isomers)]</b><br/>                 TWA: 100 ppm 8 hours.<br/>                 STEL: 150 ppm 15 minutes.<br/> <b>CA Quebec Provincial (Canada, 6/2022).</b> <b>[Xylene]</b><br/>                 TWAEV: 100 ppm 8 hours.<br/>                 TWAEV: 434 mg/m<sup>3</sup> 8 hours.<br/>                 STEV: 150 ppm 15 minutes.<br/>                 STEV: 651 mg/m<sup>3</sup> 15 minutes.<br/> <b>CA Ontario Provincial (Canada, 6/2019).</b> <b>[Xylene (o-, m-, p-isomers)]</b><br/>                 STEL: 150 ppm 15 minutes.<br/>                 TWA: 100 ppm 8 hours.<br/> <b>CA Saskatchewan Provincial (Canada, 7/2013).</b><br/> <b>[Xylene]</b><br/>                 STEL: 150 ppm 15 minutes.<br/>                 TWA: 100 ppm 8 hours.</p> |





## Section 8. Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

**Physical state** : Liquid.

**Color** : Clear.

- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point** : Technically not possible to measure
- Boiling point** : Not applicable.
- Freezing point** : Not available.
- Flash point** : Closed cup: -15°C (5°F)
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Lower: 1.2%  
Upper: 12.8%
- Vapor pressure** : 159.2 kPa (1194.4 mm Hg)
- Vapor density** : Not available.
- Relative density** : Not available.

**Partition coefficient: n-octanol/water** : Not applicable.

**Auto-ignition temperature** : 287°C (548.6°F)

**Decomposition temperature** : Not applicable.

**Viscosity** : Not available.

**Flow time (ISO 2431)** : Not available.

### Aerosol product

**Type of aerosol** : Spray

**Heat of combustion** : 28.18 kJ/g

## Section 10. Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | : No specific test data related to reactivity available for this product or its ingredients.           |
| <b>Chemical stability</b>                 | : The product is stable.   |
| <b>Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.                      |
| <b>Conditions to avoid</b>                | : Avoid all possible sources of ignition (spark or flame).   |
| <b>Incompatible materials</b>             | : No specific data.  |
| <b>Hazardous decomposition products</b>   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name | Result                | Species               | Dose                     | Exposure |
|-------------------------|-----------------------|-----------------------|--------------------------|----------|
| n-butyl acetate         | LC50 Inhalation Vapor | Rat                   | 21.1 mg/l                | 4 hours  |
|                         | LD50 Dermal           | Rabbit                | >17600 mg/kg             | -        |
|                         | LD50 Oral             | Rat                   | 10768 mg/kg              | -        |
| acetone                 | LC50 Inhalation Vapor | Rat                   | 21 mg/l                  | 4 hours  |
|                         | LD50 Dermal           | Rabbit                | 2001 mg/kg               | -        |
|                         | LD50 Oral             | Rat                   | 5800 mg/kg               | -        |
| Isopropyl alcohol       | LC50 Inhalation Vapor | Rat - Male,<br>Female | 37.5 mg/l                | 4 hours  |
|                         | LD50 Dermal           | Rabbit                | 12800 mg/kg              | -        |
|                         | LD50 Oral             | Rat                   | 5000 mg/kg               | -        |
| Isobutane               | LC50 Inhalation Vapor | Rat                   | 658000 mg/m <sup>3</sup> | 4 hours  |
| butane                  | LC50 Inhalation Vapor | Rat                   | 658000 mg/m <sup>3</sup> | 4 hours  |
| ethyl acetate           | LC50 Inhalation Vapor | Rat                   | 22.6 mg/l                | 4 hours  |
|                         | LD50 Dermal           | Rabbit                | 20001 mg/kg              | -        |
|                         | LD50 Oral             | Rat                   | 5620 mg/kg               | -        |
| XYLENE                  | LC50 Inhalation Gas.  | Rat                   | 5000 ppm                 | 4 hours  |
|                         | LD50 Oral             | Rat                   | 4300 mg/kg               | -        |
|                         | LD50 Dermal           | Rabbit                | >5 g/kg                  | -        |
| ethylbenzene            | LD50 Oral             | Rat                   | 8532 mg/kg               | -        |
|                         | LD50 Dermal           | Rabbit                | >5000 mg/kg              | -        |
|                         | LD50 Oral             | Rat                   | 3500 mg/kg               | -        |

#### Irritation/Corrosion

| Product/ingredient name | Result                   | Species | Score | Exposure        | Observation |
|-------------------------|--------------------------|---------|-------|-----------------|-------------|
| acetone                 | Eyes - Mild irritant     | Human   | -     | 186300 ppm      | -           |
|                         | Eyes - Mild irritant     | Rabbit  | -     | 10 uL           | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 20 mg  | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 20 mg           | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 395 mg          | -           |
|                         | Skin - Mild irritant     | Rabbit  | -     | 24 hours 500 mg | -           |
| Isopropyl alcohol       | Eyes - Moderate irritant | Rabbit  | -     | 10 mg           | -           |
|                         | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 100 mg | -           |
|                         | Eyes - Severe irritant   | Rabbit  | -     | 100 mg          | -           |
| XYLENE                  | Skin - Mild irritant     | Rabbit  | -     | 500 mg          | -           |
|                         | Eyes - Mild irritant     | Rabbit  | -     | 87 mg           | -           |

## Section 11. Toxicological information

|              |                          |        |   |                 |   |
|--------------|--------------------------|--------|---|-----------------|---|
| ethylbenzene | Eyes - Severe irritant   | Rabbit | - | 24 hours 5 mg   | - |
|              | Skin - Mild irritant     | Rat    | - | 8 hours 60 uL   | - |
|              | Skin - Moderate irritant | Rabbit | - | 100 %           | - |
|              | Skin - Moderate irritant | Rabbit | - | 24 hours 500 mg | - |
|              | Skin - Mild irritant     | Rabbit | - | 24 hours 15 mg  | - |

### Sensitization

Not available.

### Mutagenicity

Not available.

### Carcinogenicity

Not available.

### Reproductive toxicity

Not available.

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

| Name              | Category   | Route of exposure | Target organs                |
|-------------------|------------|-------------------|------------------------------|
| n-butyl acetate   | Category 3 | -                 | Narcotic effects             |
| acetone           | Category 3 | -                 | Narcotic effects             |
| Isopropyl alcohol | Category 3 | -                 | Narcotic effects             |
| ethyl acetate     | Category 3 | -                 | Narcotic effects             |
| XYLENE            | Category 3 | -                 | Respiratory tract irritation |

### Specific target organ toxicity (repeated exposure)

| Name         | Category   | Route of exposure | Target organs |
|--------------|------------|-------------------|---------------|
| ethylbenzene | Category 2 | -                 | -             |

### Aspiration hazard

| Name         | Result                         |
|--------------|--------------------------------|
| XYLENE       | ASPIRATION HAZARD - Category 1 |
| ethylbenzene | ASPIRATION HAZARD - Category 1 |

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness.
- Skin contact** : May cause an allergic skin reaction.
- Ingestion** : Can cause central nervous system (CNS) depression.

## Section 11. Toxicological information

### Symptoms related to the physical, chemical and toxicological characteristics

|                     |   |
|---------------------|---|
| <b>Eye contact</b>  | : Adverse symptoms may include the following:<br>pain or irritation<br>watering<br>redness  |
| <b>Inhalation</b>   | : Adverse symptoms may include the following:<br>respiratory tract irritation<br>coughing<br>nausea or vomiting<br>headache<br>drowsiness/fatigue<br>dizziness/vertigo<br>unconsciousness<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations |
| <b>Skin contact</b> | : Adverse symptoms may include the following:<br>irritation<br>redness<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations  |
| <b>Ingestion</b>    | : Adverse symptoms may include the following:<br>reduced fetal weight<br>increase in fetal deaths<br>skeletal malformations   |

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

|                                    |                  |
|------------------------------------|------------------|
| <b>Potential immediate effects</b> | : Not available. |
| <b>Potential delayed effects</b>   | : Not available. |

#### Long term exposure

|                                    |                  |
|------------------------------------|------------------|
| <b>Potential immediate effects</b> | : Not available. |
| <b>Potential delayed effects</b>   | : Not available. |

#### Potential chronic health effects

Not available.

|                              |   |
|------------------------------|---|
| <b>General</b>               | : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| <b>Carcinogenicity</b>       | : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.              |
| <b>Mutagenicity</b>          | : No known significant effects or critical hazards.   |
| <b>Teratogenicity</b>        | : Suspected of damaging the unborn child.   |
| <b>Developmental effects</b> | : No known significant effects or critical hazards.   |
| <b>Fertility effects</b>     | : Suspected of damaging fertility.  |

### Numerical measures of toxicity

## Section 11. Toxicological information

### Acute toxicity estimates

| Route              | ATE value      |
|--------------------|----------------|
| Oral               | 30472.18 mg/kg |
| Dermal             | 5937.25 mg/kg  |
| Inhalation (gases) | 181152.07 ppm  |





## Section 12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses waterways.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## Section 14. Transport information

|                            | TDG Classification   | DOT Classification   | IMDG  | IATA   |
|----------------------------|--|--|---|--|
| UN number                  | UN1950   | UN1950   | UN1950  | UN1950   |
| UN proper shipping name    | AEROSOLS   | AEROSOLS   | AEROSOLS  | Aerosols, flammable  |
| Transport hazard class(es) | 2.1<br> | 2.1<br> | 2.1<br> | 2.1<br> |
| Packing group              | -  | -  | -   | -  |
| Environmental hazards      | No.  | No.  | No.   | No.  |

### Additional information

- TDG Classification** : Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).
- DOT Classification** : **Reportable quantity** 4292.2 lbs / 1948.7 kg [679.14 gal / 2570.8 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

## Section 14. Transport information

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

## Section 15. Regulatory information

### Canadian lists

**Canadian NPRI** : The following components are listed: butyl acetate (all isomers); propane; isopropyl alcohol; butane (all isomers); butane (all isomers); ethyl acetate; xylene (all isomers); propylene glycol methyl ether acetate

**CEPA Toxic substances** : None of the components are listed.

### Inventory list

**Canada** : All components are listed or exempted.

**United States** : All components are listed or exempted.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

|                  |   |   |
|------------------|---|---|
| Health           | * | 2 |
| Flammability     |   | 3 |
| Physical hazards |   | 3 |
|                  |   |   |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### History

**Date of issue** : 2/12/2024

**Version** : 18

Product stewardship and regulatory compliance.

## Section 16. Other information

**Key to abbreviations** : ATE = Acute Toxicity Estimate  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
UN = United Nations  
HPR = Hazardous Products Regulations

✔ Indicates information that has changed from previously issued version.

### Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.