









Axalta™ VS1150 Aerosol Surface Cleaning Solvent

 VS1150 Aerosol Surface Cleaning Solvent COMPONENTS	 Spray on surface APPLICATION
 Ready to Use MIX RATIO	 Wipe dry with clean cloth DRY TIME
 N/A VISCOSITY	 743 grams / liter 6.2 lbs / gallon VOC



GENERAL

DESCRIPTION

Axalta VS1150 is an aerosol cleaning solvent suitable for removing sanding dust, tar, finger prints, wax and a small amount of silicone, oil or grease. Ideal for small repairs.

The products referenced herein may not be sold in your market. Please consult your distributor for product availability.



MIXING

Ready to use



APPLICATION

SUBSTRATE

OEM painted surface, cured paint, bare metal. Do not use over plastic or fiberglass due to potential for static buildup which could cause a flash fire.

APPLICATION:

- Apply to the surface.
- Immediately wipe dry with a clean cloth.
- Repeat as needed to remove contaminants.
- Replace cap to prevent potential misuse.

TIPS FOR SUCCESS:

Spray pressure will be lost during extended application. Shake the can or allow the can to rest for a few minutes to re-establish pressure.



PHYSICAL PROPERTIES

Max. VOC (AP):	743 g/L (6.2 lbs./gal)
Avg. Gallon Weight:	783 g/L (6.54 lbs./gal)
Avg. Weight % Volatiles:	100%
Avg. Weight % Water:	0.0%
Avg. Weight % Exempt Solvent:	0.0%
Avg. Volume % Water:	0.0%
Avg. Volume % Exempt Solvent:	0.0%
Flash Point:	See SDS

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS/MSDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: February 2021

In the United States and Canada:

1.855.6.AXALTA

Axalta.us

