

# 1. Identification of the substance/mixture and of the company/undertaking

Product name GREEN FAST PIPE POWDER

Product code 72508FG Formula Date: 2015-02-20

Intended use Coating powder for professional use

Powder application by electrostatic spraying

Axalta Powder Coating Systems USA, Inc.

9800 Genard Rd

US Houston, TX 77041

**Telephone** Product information (800) 438-3876

Medical emergency (855) 274-5698

Transportation emergency (800) 424-9300 (CHEMTREC)

## 2. Hazards identification

This preparation is hazardous per the following GHS criteria

#### **GHS-Classification**

Serious eye damage/eye irritation Category 2A

Endpoints which are ""not classified"", ""cannot classified"" and ""not applicable"" are not shown

## **GHS-Labelling**

Hazard symbols

Signal word Warning

Hazard statements Causes serious eye irritation.

Precautionary statements Wear eye protection/ face protection.

If eye irritation persists: Get medical advice/ attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

## Other hazards which do not result in classification

Contains epoxy constituents. See information supplied by the manufacturer.

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity:

# 3. Composition/information on ingredients

Mixture of synthetic resins and pigments

#### Components

| CAS-No.     | Chemical Name    | Concentration |
|-------------|------------------|---------------|
| 13983-17-0  | Calcium silicate | 26 - 37%      |
| 138265-88-0 | Zinc horate      | 1 - 4%        |

72508FG v4.0 en/US



| <br>CAS-No. | Chemical Name     | Concentration |
|-------------|-------------------|---------------|
| 693-98-1    | 2-methylimidazole | 0.0 - 1.0%    |

Non-regulated ingredients 70 - 80%

OSHA Hazardous: Yes

## 4. First aid measures

#### Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

#### Skin contact

Do NOT use solvents or thinners. Take off contaminated clothing and shoes immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

#### Inhalation

Avoid breathing dust. Inhalation of dust may cause shortness of breath, tightness of the chest, a sore throat and cough. Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.

#### Ingestion

If swallowed, seek medical advice immediately and show this container or label.

#### Most Important Symptoms/effects, acute and delayed

#### Inhalation

Dust generated from this product may be irritating to the respiratory tract.

#### Ingestion

May result in gastrointestinal distress.

## Skin or eye contact

Dust generated from this product may cause irritation of the eyes. Repeated or prolonged contact may cause skin irritation with discomfort and dermatitis.

## Indication of Immediate medical attention and special treatment needed if necessary

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

## 5. Firefighting measures

## Suitable extinguishing media

Water sprayDry chemical

### Extinguishing media which shall not be used for safety reasons

High volume water jet

## **Hazardous combustion products**

CO, CO2, smoke, and oxides of any heavy metals that are reported in "Composition, Information on Ingredients" section.

## Fire and Explosion Hazards

The product is not flammable. The product itself does not burn.

72508FG v4.0 en/US



#### Special Protective Equipment and Fire Fighting Procedures

Full protective flameproof clothing should be worn as appropriate. Wear self contained breathing apparatus for fire fighting if necessary. In the event of fire, cool tanks with water spray. Do not allow run-off from fire fighting to enter public sewer systems or public waterways.

## 6. Accidental release measures

#### Procedures for cleaning up spills or leaks

Sweep up material and dispose of properly. Avoid breathing any dust that might be generated. Spills of fine material should be cleaned using gentle sweeping or vacuuming. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.

### **Environmental precautions**

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

# 7. Handling and storage

#### Precautions for safe handling

Observe label precautions. Close container after each use. Do not transfer contents to unlabeled containers. Wash thoroughly after handling and before eating or smoking. Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits. Keep away from open flames, hot surfaces and sources of ignition. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources.

If material is a coating: do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves. Combustible dust clouds may be created where operations produce fine material (dust). Avoid formation of significant deposits of material as they may become airborne and form combustible dust clouds. Build up of fine material should be cleaned using gentle sweeping or vacuuming in accordance with best practices. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used.

## Advice on protection against fire and explosion

Always keep in containers of same material as the original one. Airborne dusts are potentially explosive. Avoid formation of significant deposits of material as they may become airborne and form combustible dust clouds. Handling and processing operations should be conducted in accordance with best practices (e.g.NFPA-654). Never use pressure to empty container: container is not a pressure vessel. The accumulation of contaminated rags may result in spontaneous combustion. Good housekeeping standards and regular safe removal of waste materials will minimize the risks of spontaneous combustion and other fire hazards.

#### Storage

#### Requirements for storage areas and containers

Observe label precautions. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

## Advice on common storage

Store separately from oxidizing agents and strongly alkaline and strongly acidic materials.

# 8. Exposure controls/personal protection

#### Engineering controls and work practices

Do not breathe dust. Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible-by the use of a local exhaust ventilation. If these are not sufficient to maintain exposure to dusts below the OEL, suitable respiratory protection must be worn.

### National occupational exposure limits

72508FG v4.0 en/US



| CAS-No.    | Chemical Name    |        | Time           | Type | Value   | Note                               |
|------------|------------------|--------|----------------|------|---------|------------------------------------|
|            |                  | Source |                | •    |         |                                    |
| 13983-17-0 | Calcium silicate | Dupont | 8 & 12<br>hour | TWA  | 5 mg/m3 | non fibrous<br>particulate<br>None |

<sup>\*\*</sup> TWA = Time-weighted average.

## **Protective equipment**

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

## Respiratory protection

Should any dust be generated, it should not be breathed. If a respirator is needed to meet applicable exposure limits, wear a properly fitted air-purifying respirator approved by NIOSH. Follow respirator manufacturers directions for respirator use. Do not breathe dust. If respirator is required to meet applicable exposure limits, use a NIOSH approved TC-84A respirator in accordance with regulatory requirements (in the US follow OSHA standard 29CFR1910.134) and the respirator manufacturer's directions.

#### Eye protection

Desirable in all industrial situations.

## Skin and body protection

Gloves are recommended

#### Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.

## **Environmental exposure controls**

Do not let product enter drains. For ecological information, refer to Ecological Information Section 12.

# 9. Physical and chemical properties

## **Appearance**

Form: solid Colour: green

Flash point Not applicable. Lower Explosive Limit Not applicable. Upper Explosive Limit Not applicable. Evapouration rate not applicable Vapor pressure of principal solvent 0.0 hPa Water solubility moderate Vapor density of principal solvent (Air = 1) Not applicable. Approx. Boiling Range Not applicable. Not applicable. Approx. Freezing Range 12.23 1.47

Gallon Weight (lbs/gal)

Specific Gravity

Percent Volatile By Volume

Percent Volatile By Weight

Percent Solids By Volume

Percent Solids By Weight

Percent Solids By Weight

pH (waterborne systems only)

Partition coefficient: n-octanol/water

Ignition temperature

12.23

1.47

0.01%

0.01%

99.99%

99.99%

not applicable

no data available

Not applicable.

Ignition temperature Not applicable.

Decomposition temperature Not applicable.

Viscosity (23 °C) Not applicable.

VOC\* less exempt (lbs/gal) 0.0 VOC\* as packaged (lbs/gal) 0.0

DIN 51794 ISO 2431-1993

© 2015 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.

72508FG v4.0 en/US



Does not sustain combustion.

\* VOC less exempt (theoretical) and VOC as packaged (theoretical) are based upon the VOC of the packaged material at the point of manufacture.

# 10. Stability and reactivity

## Stability

Stable

#### Conditions to avoid

Stable under recommended storage conditions.

#### Materials to avoid

None reasonably foreseeable.

#### Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

## **Hazardous Polymerization**

Will not occur.

#### Sensitivity to Static Discharge

no data available

### **Sensitivity to Mechanical Impact**

None known.

# 11. Toxicological information

#### Information on likely routes of exposure

#### Inhalation

Dust generated from this product may be irritating to the respiratory tract.

#### Ingestion

May result in gastrointestinal distress.

#### Skin or eye contact

Dust generated from this product may cause irritation of the eyes. Repeated or prolonged contact may cause skin irritation with discomfort and dermatitis.

# Delayed and immediate effects and also chronic effects from short and long term exposure:

## Acute oral toxicity

Not classified according to GHS criteria

#### Acute dermal toxicity

Not classified according to GHS criteria

#### Acute inhalation toxicity

Not classified according to GHS criteria

72508FG v4.0 en/US



#### Skin corrosion/irritation

Not classified according to GHS criteria

## Serious eye damage/eye irritation

Calcium silicate Category 2B 2-methylimidazole Category 1

## Respiratory sensitisation

Not classified according to GHS criteria

#### Skin sensitisation

Not classified according to GHS criteria

## Germ cell mutagenicity

Not classified according to GHS criteria

## Carcinogenicity

Not classified according to GHS criteria

## **Toxicity for reproduction**

Not classified according to GHS criteria

#### Target Organ Systemic Toxicant - Single exposure

Not classified according to GHS criteria

### Target Organ Systemic Toxicant - Repeated exposure

Not classified according to GHS criteria

## **Aspiration toxicity**

Not classified according to GHS criteria

## Numerical measures of toxicity (acute toxicity estimation (ATE),etc. )

No information available.

# Symptoms related to the physical, chemical and toxicological characteristics

No information available.

## Whether the hazardous chemical is listed by NTP, IARC or OSHA

Titanium dioxide (rutile) IARC 2B 2-methylimidazole IARC 2B

# 12. Ecological information

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

# 13. Disposal considerations

## **Waste Disposal Method**

Do not allow material to contaminate ground water systems. Incinerate or otherwise dispose of waste material in accordance with Federal, State, Provincial, and local requirements. Do not incinerate in closed containers.

72508FG v4.0 en/US



# 14. Transport information

Not classified as dangerous in the meaning of transport regulations.

## Matters needing attention for transportation

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

# 15. Regulatory information

## **TSCA Status**

In compliance with TSCA Inventory requirements for commercial purposes.

#### **DSL Status**

Product is not DSL listed because one or more ingredients are not on the DSL inventory.

#### **Photochemical Reactivity**

Non-photochemically reactive

## US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

WARNING! This product contains a chemical known to the State of California to cause cancer.

## Regulatory information

|             |                   |     |     |    | RA      |     | CERCLA  | CAA |
|-------------|-------------------|-----|-----|----|---------|-----|---------|-----|
| CAS#        | Ingredient        | 302 | TPQ | RQ | 311/312 | 313 | RQ(lbs) | HAP |
| 13983-17-0  | Calcium silicate  | N   | NR  | NR | NA      | N   | NR      | N   |
| 138265-88-0 | Zinc borate       | N   | NR  | NR | NA      | Ν   | NR      | N   |
| 693-98-1    | 2-methylimidazole | N   | NR  | NR | NA      | Ν   | NR      | Ν   |

## Key:

| EPCRA                                  | Emergency Planning and Community Right-to-know Act (aka Title III, SARA)  |  |  |  |
|--|---|--|--|--|
| 302                                    | Extremely hazardous substances  |  |  |  |
| 311/312 Categories                     | F = Fire Hazard<br>R = Reactivity Hazard<br>P = Pressure Related Hazard   | A = Acute Hazard<br>C = Chronic Hazard |  |  |
| 313 Information                        | Section 313 Supplier Notification - The chemicals listed above with a 'Y' in the 313 column are subject to reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know act of 1986 and of 40 CFR 372. |  |  |  |
| CERCLA<br>HAP<br>TPQ<br>RQ<br>NA<br>NR | Comprehensive Emergency Response, Compensation and Liability Act of 1980. Listed as a Clean Air Act Hazardous Air Pollutant. Threshold Planning Quantity. Reportable Quantity not available not regulated                             |  |  |  |

# 16. Other information

HMIS rating H: 1 F: 0 R: 0

72508FG v4.0 en/US



#### Glossary of Terms:

ACGIH | American Conference of Governmental Industrial Hygienists.

IARC International Agency for Research on Cancer.

NTP National Toxicology Program.
OEL Occupational Exposure Limit

OSHA Occupational Safety and Health Administration.

STEL Short term exposure limit.
TWA Time-weighted average.

PNOR Particles not otherwise regulated.
PNOC Particles not otherwise classified.

NOTE: The list (above) of glossary terms may be modified.

#### Notice from Axalta Coating Systems

The document reflects information provided to Axalta Coating Systems by its suppliers. Information is accurate to the best of our knowledge and is subject to change as new data is received by Axalta Coating Systems. Persons receiving this information should make their own determination as to its suitability for their purposes prior to use. The information on this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. SDS prepared by:

Axalta Coating Systems Regulatory Affairs

Report version

Version Changes
4.0 2, 3, 4, 5, 6, 7, 8, 9, 11, 14, 15

Revision Date: 2015-05-13

