

## **Technical Information Sheet**

## ALESTA AR500\*

Number: FFB612U3

October 29, 2020

Name: *AR500 8N2605 Black* 

Type: Proprietary

Alesta Group Code: FP30004000616

**POWDER PROPERTIES** 

ASTM D5965-96, C

Specific Gravity  $1.49 \pm 0.05$ 

Theoretical Coverage 129 ft 2/lb/mil

Recommended Shelf Life: 12 Months @ 75°F

**COATING PROPERTIES** 

**ASTM D523-89** *Gloss at 60°* 

30-40

DPC TM 10.219 ASTM D2454-95 PCI Powder Smoothness 7
Overbake Resistance, Time 10

100% 2H

ASTM D3363-92a ASTM D2794-93 Pencil Hardness Direct Impact, Gardner

30 in/lbs 5B Pass

ASTM D3359-97

Adhesion, Cross Hatch Flexibility, Mandrel

1/8 in. dia., no fracture

ASTM D522-93a ASTM B117-97

Salt Spray

4000 hrs

AAMA 2605-05

Superior Performance Organic

Coatings on Aluminum

Extrusions

Passed

#### **APPLICATION**

Electrostatic Spray, Cold Substrate: Aluminum

Pretreatment: Chrome Phosphate or other AAMA approved Pre-treatment

CURE SCHEDULE:

(Time at substrate temperature)

20 Minutes @ 400°F

FILM THICKNESS: 2.0-3.0 Mils

Recommended for use in architectural applications such as window frames, cladding, shopfronts and other products where superior levels of exterior weatherability are required. This product meets requirements for AAMA 2605 as per the American Architectural Manufacturers Association and is based on proven fluoropolymer technology used globally in architectural market. The metallic component of this product is incorporated into the powder, vastly improving application and reclaim behavior when compared to traditional metallic coating powders.

Prepared 11/23/2020

#### **ROHS**

9800 Genard Rd. Houston, TX 77041-7624 4130 Lyman Dr. Hilliard, OH 43026-1213 1-800-247-3886 fax: 713-939-4027 1-800-667-9610 fax: 614-771-4139 TOUGH

ISO 9001:2015

WARRANTY POLICY: Seller certifies that all coatings delivered to Customer in unopened factory filled containers meet all pertinent quality standards presented in its current published literature. Since matters of surface preparation, application procedures, curing procedures and other local factors that affect coating performance are beyond Seller's control, Seller assumes no liability for coating failure other than to supply replacement material or a coating material proven to be defective. Customer will determine suitability of this product for its use and thereby assume all risks and liabilities in connection therewith. Seller will not be liable for any injuries, damages or other losses derived, directly or indirectly, from or as a consequence of Customer's use of the product. SELLER DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, RELATING TO ITS PRODUCTS AND THEIR APPLICATION, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSES.





# **Technical Information Sheet**

## ALESTA AR500\*

Number: FFB612U3

Alesta Group Code: FP30004000616

Axalta does not intentionally add any RoHS restricted substances to this product, and the product is in conformity with the essential requirements of the following directives of the European Parliament and of the Council: Directive 2015/863; Directive 2011/65/EU; Directive 2002/65/EU; and, Directive 2003/11/EU.

9800 Genard Rd. Houston, TX 77041-7624 4130 Lyman Dr. Hilliard, OH 43026-1213 1-800-247-3886 fax: 713-939-4027 1-800-667-9610 fax: 614-771-4139



ISO 9001:2015

WARRANTY POLICY: Seller certifies that all coatings delivered to Customer in unopened factory filled containers meet all pertinent quality standards presented in its current published literature. Since matters of surface preparation, application procedures, curing procedures and other local factors that affect coating performance are beyond Seller's control, Seller assumes no liability for coating failure other than to supply replacement material or a coating material proven to be defective. Customer will determine suitability of this product for its use and thereby assume all risks and liabilities in connection therewith. Seller will not be liable for any injuries, damages or other losses derived, directly or indirectly, from or as a consequence of Customer's use of the product. SELLER DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, RELATING TO ITS PRODUCTS AND THEIR APPLICATION, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSES.

