

Technical Information Sheet

Fas-Trac Service

NUMBER: PFHF191S1

August 27, 2020

NAME: FS 36440 Matte

Type: TGIC-Polyester

POWDER PROPERTIES

ASTM D5965-96, C Specific Gravity

1.49 ± 0.05

Theoretical Coverage

129 ft²/lb/mil

ASTM D3451-92, 13 Mass Loss During Cure

< 1 % 18 Months @

75°F

Recommended Shelf Life:

COATING PROPERTIES

ASTM D523-89 Gloss at 60°

3-8

`

DPC TM 10.219

PCI Powder Smoothness

Dir / Rev Impact, Gardner

6 2H

ASTM D3363-92a Pencil Hardness

100 / 100 in/lbs

ASTM D2794-93 ASTM D522-93a

Flexibility, Mandrel

1/4 in. dia., no fracture

ASTM B117-97

Salt Spray

1,000 hrs

UL DTOV2 Organic Coating

Steel Enclosures, Elect. Eq.

Recognized

APPLICATION

Electrostatic Spray, Cold

Substrate: 0.032 in. CRS

Pretreatment: Bonderite 1000®, Parcolene® 60

This is an Axalta Powder Coating Systems USA Fas-Trac product.

Cure Schedule:

(Time at substrate temperature)

10 Minutes @ 400°F

Film Thickness: 2.0-3.0 Mils

Prepared 8/27/2020

ROHS

Axalta does not intentionally add any RoHS restricted substances to this product, and the product is in conformity with the essential requirements of the following directives of the European Parliament and of the Council: Directive 2015/863; Directive 2011/65/EU; Directive 2002/65/EU; and, Directive 2003/11/EU.

9800 Genard Rd. Houston, TX 77041-7624 4130 Lyman Dr. Hilliard, OH 43026-1213 1-800-247-3886 1-800-667-9610 fax: 713-939-4027 fax: 614-771-4139 TOUGH ISO 9001:2015

WARRANTY POLICY: Seller certifies that all coatings delivered to Customer in unopened factory filled containers meet all pertinent quality standards presented in its current published literature. Since matters of surface preparation, application procedures, curing procedures and other local factors that affect coating performance are beyond Seller's control, Seller assumes no liability for coating failure other than to supply replacement material for a coating material proven to be defective. Customer will determine suitabilities in connection therewith. Seller will not be liable for any injuries, damages or other losses derived, directly or indirectly, from or as a consequence of Customer's use of the product. SELLER DISCLAIMS ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, RELATING TO ITS PRODUCTS AND THEIR APPLICATION, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSES.

