

US: ENGLISH

## SAFETY DATA SHEET

# **Section 1. Identification**

Product identifier : 1255

Product name : Tufcote Hydro 2.1 HG 1255 Clear

**Date of issue** : 2/7/2024

Version : 8

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Coating component.

**Uses advised against** : Not for sale to or use by consumers.

Supplier's details : Axalta Coating Systems, LLC

50 Applied Bank Blvd.

Suite 300

Glen Mills, PA 19342

USA

**Product information** 855-6AXALTA

**Emergency telephone** 

number

: (CHEMTREC) - 800-424-9300

# Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the : SKIN SENSITIZATION - Category 1

substance or mixture TOXIC TO REPRODUCTION - Category 1B

**GHS label elements** 

Hazard pictograms :





Signal word : Danger

**Hazard statements** : H317 - May cause an allergic skin reaction.

H360 - May damage fertility or the unborn child.

**Precautionary statements** 

**Prevention**: P201 - Obtain special instructions before use.

P280 - Wear protective gloves, protective clothing and eye or face protection.

P261 - Avoid breathing vapor.

**Response**: P308 + P313 - IF exposed or concerned: Get medical advice or attention.

P363 - Wash contaminated clothing before reuse. P302 + P352 - IF ON SKIN: Wash with plenty of water.

P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

Storage : Not applicable.

## Section 2. Hazards identification

**Disposal** 

: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

: None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	CAS number	Concentration
<b>2</b> -butoxyethanol	111-76-2	≤8.2
BUTYL BENZYL PHTHALATE	85-68-7	≤3
2-(2-butoxyethoxy)ethanol	112-34-5	≤1.7
BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATE	41556-26-7	≤1
Poly(oxy-1,2-ethanediyl), $\alpha$ -[3-[3-(2H-benzotriazol-2-yl) -5- (1,1-dimethylethyl)-4- hydroxyphenyl] -1-oxopropyl]- $\omega$ -hydroxy-		≤0.3
ULTRAVIOLET ABSORBER	104810-47-1	≤0.3
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	≤0.3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

#### **Description of necessary first aid measures**

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

## Section 4. First aid measures

#### Ingestion

: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

## Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

**Eye contact** : No specific data.

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

**Protection of first-aiders**: No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

See toxicological information (Section 11)

# **Section 5. Fire-fighting measures**

#### **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing

apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

# including any incompatibilities

Conditions for safe storage, : Store between the following temperatures: 5 to 30°C (41 to 86°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Storage code : IIIB

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits		
2-butoxyethanol	ACGIH TLV (United States, 1/2023).		
•	TWA: 20 ppm 8 hours.		
	OSHA PEL 1989 (United States, 3/1989). Absorbed		
	through skin.		
	TWA: 25 ppm 8 hours.		
	TWA: 120 mg/m³ 8 hours.		
	NIOSH REL (United States, 10/2020). Absorbed		
	through skin.		
	TWA: 5 ppm 10 hours.		
	TWA: 24 mg/m³ 10 hours.		
	OSHA PEL (United States, 5/2018). Absorbed through		
	skin.		
	TWA: 50 ppm 8 hours.		
	TWA: 240 mg/m³ 8 hours.		
	CAL OSHA PEL (United States, 5/2018). Absorbed		
	through skin.		
	TWA: 97 mg/m³ 8 hours.		
	TWA: 20 ppm 8 hours.		
BUTYL BENZYL PHTHALATE	None.		

# Section 8. Exposure controls/personal protection

2-(2-butoxyethoxy)ethanol	ACGIH TLV (United States, 1/2023). TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor
BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATE	None.
Poly(oxy-1,2-ethanediyl), α-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4- hydroxyphenyl] -1-oxopropyl]-ω - hydroxy-	None.
ULTRAVIOLET ABSORBER	None.
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	None.

# Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

# Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with sideshields.

## Skin protection

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 9. Physical and chemical properties

**Appearance** 

**Physical state** : Liquid. Color : Clear.

Odor : Not available. : Not available. Odor threshold

Hq : 5 to 10

**Melting point** : Technically not possible to measure : 100 to 173°C (212 to 343.4°F) **Boiling point** 

Flash point : Closed cup: 93.889°C (201°F) [Product does not sustain combustion.]

**Evaporation rate** : Not available. Flammability (solid, gas) : Not available. Lower and upper explosive : Lower: 1.1% Upper: 10.6% (flammable) limits

Vapor pressure : 1.1 kPa (8.3 mm Hg)

Vapor density : Not available. **Density** : 1.032 g/cm<sup>3</sup>

Solubility(ies)

Media	Result
cold water	Soluble

Partition coefficient: n-

octanol/water

: Not applicable.

**Auto-ignition temperature** : 210°C (410°F) **Decomposition temperature**: Not applicable. **Viscosity** : Not available. Flow time (ISO 2431) : Not available.

# Section 10. Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. Reactivity

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data. Incompatible materials : No specific data.

**Hazardous decomposition** 

: Under normal conditions of storage and use, hazardous decomposition products should

products not be produced.

# **Section 11. Toxicological information**

## Information on toxicological effects

**Acute toxicity** 

# Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
2-butoxyethanol	LD50 Dermal	Rat	2010 mg/kg	-
	LD50 Oral	Rat	917 mg/kg	-
BUTYL BENZYL PHTHALATE	LD50 Dermal	Rabbit	>10000 mg/kg	-
	LD50 Dermal	Rat	6700 mg/kg	-
	LD50 Oral	Rat	2330 mg/kg	-
2-(2-butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-

## **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
<b>2</b> -butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
	Skin - Mild irritant	Rabbit	_	mg 500 mg	_
2-(2-butoxyethoxy)ethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 20	-
	Eyes - Severe irritant	Rabbit	-	mg 20 mg	-

### **Sensitization**

Not available.

## **Mutagenicity**

Not available.

## Carcinogenicity

Not available.

### **Classification**

Product/ingredient name	OSHA	IARC	NTP
2-butoxyethanol	-	3	-
BUTYL BENZYL	-	3	-
PHTHALATE			

## **Reproductive toxicity**

Not available.

## **Teratogenicity**

Not available.

## Specific target organ toxicity (single exposure)

Not available.

## Specific target organ toxicity (repeated exposure)

Not available.

## **Aspiration hazard**

Not available.

# **Section 11. Toxicological information**

Information on the likely

routes of exposure

: Not available.

#### Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact**: May cause an allergic skin reaction.

**Ingestion**: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : No specific data.

**Inhalation** : Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

**Skin contact**: Adverse symptoms may include the following:

irritation redness

reduced fetal weight increase in fetal deaths skeletal malformations

**Ingestion**: Adverse symptoms may include the following:

reduced fetal weight increase in fetal deaths skeletal malformations

## Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

**Potential immediate** 

effects

: Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : No known significant effects or critical hazards.Mutagenicity : No known significant effects or critical hazards.

**Teratogenicity** : May damage the unborn child.

**Developmental effects**: No known significant effects or critical hazards.

Fertility effects : May damage fertility.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

# Section 11. Toxicological information

Route	ATE value
Oral	10054.79 mg/kg
Dermal	12863.4 mg/kg
Inhalation (vapors)	139.39 mg/l

# **Section 12. Ecological information**

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses waterways.

# Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# **Section 14. Transport information**

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN3082	UN3082	UN3082	UN3082	UN3082
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (PAINT)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	SUBSTANCIA LIQUIDA POTENCIALMENTE PELIGROSA PARA EL MEDIO AMBIENTE, N.E. P.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BUTYL BENZYL PHTHALATE)	Environmentally hazardous substance, liquid, n.o.s. (BUTYL BENZYL PHTHALATE)
Transport hazard class(es)	9	9	9	9	9
Packing group	III	III	III	III	III
Environmental hazards	Yes.	Yes.	Yes.	Yes.	Yes.

### **Additional information**

# **Section 14. Transport information**

DOT Classification

: Non-bulk packages of this product are not regulated as hazardous materials in package sizes less than the product reportable quantity, unless transported by inland waterway. The marine pollutant mark is not required when transported on inland waterways in sizes of ≤5 L or ≤5 kg.

Reportable quantity 4381.1 lbs / 1989 kg [509.15 gal / 1927.3 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

**Limited quantity** Yes.

Packaging instruction Exceptions: 155. Non-bulk: 203. Bulk: 241. **Special provisions** 8, 146, 173, 335, 441, IB3, T4, TP1, TP29

**TDG Classification** 

: Product classified as per the following sections of the Transportation of Dangerous

Goods Regulations: 2.43-2.45 (Class 9), 2.7 (Marine pollutant mark).

Non-bulk packages of this product are not regulated as dangerous goods when

transported by road or rail.

**Explosive Limit and Limited Quantity Index** 5

Special provisions 16, 99

**Mexico Classification** 

: The environmentally hazardous substance mark is not required when transported in

sizes of ≤5 L or ≤5 kg.

Special provisions 274, 331, 335

**IMDG** 

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and

4.1.1.4 to 4.1.1.8.

Emergency schedules F-A, S-F Special provisions 274, 335, 969

IATA

: This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

Quantity limitation Passenger and Cargo Aircraft: 450 L. Packaging instructions: 964. Cargo Aircraft Only: 450 L. Packaging instructions: 964. Limited Quantities - Passenger

Aircraft: 30 kg. Packaging instructions: Y964. Special provisions A97, A158, A197, A215

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

# Section 15. Regulatory information

Clean Air Act Section 112 : Listed

(b) Hazardous Air **Pollutants (HAPs)** 

**SARA 304 RQ** 

**SARA 304 RQ** 

: 153899.9 lbs / 69870.6 kg [17885.5 gal / 67704 L]

**SARA 311/312** 

Date of issue: 2/7/2024 Version: 8 11/13

1255

# Section 15. Regulatory information

Classification : SKIN SENSITIZATION - Category 1

TOXIC TO REPRODUCTION - Category 1B

#### **SARA 313**

US: ENGLISH

	Product name	CAS number	%
Form R - Reporting requirements		111-76-2 112-34-5	≤8.2 ≤1.7
Supplier notification	— ····································	111-76-2 112-34-5	≤8.2 ≤1.7

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

#### **Inventory list**

Canada : At least one component is not listed.
United States : All components are listed or exempted.

# Section 16. Other information

#### **Hazardous Material Information System (U.S.A.)**



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

## National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### **History**

**Date of issue** : 2/7/2024

Version : 8

Product stewardship and regulatory compliance.

## Section 16. Other information

Key to abbreviations

: ATE = Acute Toxicity Estimate

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

✓ Indicates information that has changed from previously issued version.

#### Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.