






# Metacryl 7349 Matting Base




**7349 Matting Base**  
COMPONENTS




N/A  
APPLICATION




**Ready to Use**  
MIX RATIO



N/A  
DRY TIME



N/A  
VISCOSITY



2.1 lbs/gal  
251 g/L  
VOC



## GENERAL

### DESCRIPTION

Metacryl 7349 Universal 2.1 VOC Matting Base is a specially formulated product designed only for the Metacryl range as a post addition additive.

The products referenced herein may not be sold in your market. Please consult your distributor for product availability.



## MIXING

### COMPONENTS

Shake can prior to use. Product is ready-to-spray.

#### Component

Metacryl 7349 Matting Base

#### Volume

1

### MIX RATIOS FOR FINISH

**FOR FLAT:** (0 – 15 Gloss)

3 Parts RFU Clear or Color : 2 Parts 7349

**FOR SATIN:** (20 – 45 Gloss)

2 Parts RFU Clear or Color: 1 Part 7349

**FOR SEMI:** (50 – 65 Gloss)

3 Parts RFU Clear or Color: 1 Part 7349



## APPLICATION

Refer to main components application instructions.



**CLEAN-UP**

Clean spray equipment immediately following application with a quality thinner or spray gun cleaner. Dispose of all paint and paint related materials in accordance with state and local regulations.



**PHYSICAL PROPERTIES**

VOC as Applied	2.1 lbs./gallon (251 g/L)
Weight Solids	8.75%
Product Class	Specialty product

**STORAGE CONDITIONS**

Store in a dry, well ventilated area. Storage temperatures should be between -30°F (-34°C) and 120°F (48°C).

**VOC REGULATED AREAS**

VOC as Applied	251 grams/liter   2.1 lbs/gallon
----------------	----------------------------------

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

**SAFETY AND HANDLING**

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: May 2019

In the United States and Canada:  
**1.855.6.AXALTA**  
**metacryl.us**

