



Metalux™ 9331 Plastic Prep Solution



GENERAL

DESCRIPTION

9331 Plastic Prep Solution is designed to aid with the adhesion of primer and topcoats over difficult bare plastics, when used as a system with Metalux™ 3812 Polypropylene Primer, Metalux 8850NF Polypropylene Adhesion Promoter/Sealer.

DO NOT use on polycarbonate (Lexan).

Package Sizes

- 1 quart (0.94 liters)



APPLICATION

SURFACE PREPARATION

Clean surface with 9331 using a clean lint free wipe. Scuff the panel with 9331 and a grey scuff pad or a grey scuff pad with water and sanding paste. Rise with warm water. Re-clean with 9331 or 9145.

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: July 2018

In the United States and Canada:

1.855.6.AXALTA
metalux.us

