



# Metalux™ 9743 Zero VOC Degreaser



---

## GENERAL

### DESCRIPTION

Metalux™ 9743 Zero VOC Degreaser has been designed specifically as a waterborne surface cleaner for areas with Low VOC regulations. 9743 is used to remove tar, wax, oil, grease, road grime, silicone and surface contaminants prior to sanding or body work. Can be used to bare metal without concern for immediate flash rusting and is recommended for use on substrates prone to static build up such as plastic bumper covers (polypropylene).

### Package Sizes

- 1 gallon (3.75 liters)



---

## APPLICATION

### APPLICATION

Clean thoroughly using fresh 9743 to ensure that the surface is clean and free of contamination. Use a silicone-free wipe to apply. Do not place wipe on opening of container as contamination could occur. Pour 9743 onto the wipe or into a separate container and use from this container and then discard. Wipe in one direction followed up with a separate clean wipe drying in the same direction. Clean article in sections making sure to dry thoroughly. Galvanized metal - red scuff then clean with the above application process; followed by a hot water rinse and an immediate towel dry with a clean, lint-free cloth.

---

## VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

---

## SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: July 2018

In the United States and Canada:

**1.855.6.AXALTA**  
**metalux.us**

