



Metalux™ Universal Reducers



GENERAL

DESCRIPTION

Universal Reducers 1156-58 are designed exclusively to be used in the complete range of Metalux™ products; 2K Primers, Sealers, Clearcoats, and both Basecoat & 2K SS Color Systems.

Package Sizes

- 1 quart (0.94 liters)
- 1 gallon (3.75 liters)
- 5 gallon (18.96 liters)



APPLICATION

APPLICATION

Mix solvent with Metalux Refinish Products in accordance with the product TDS.

Based on ambient temperature:

1156 Fast: 60°-73°F / 16°-23°C

1157 Medium: 74°-92°F / 23°-33°C

1158 Slow: 93°F+ / 34°C+

VOC REGULATED AREAS

These directions refer to the use of products which may be restricted or require special mixing instructions in VOC regulated areas. Follow mixing usage and recommendations in the VOC Compliant Products Chart for your area.

SAFETY AND HANDLING

For industrial use only by professional, trained painters. Not for sale to or use by the general public. Before using, read and follow all label and SDS precautions. If mixed with other components, mixture will have hazards of all components.

Ready to use paint materials containing isocyanates can cause irritation of the respiratory organs and hypersensitive reactions. Asthma sufferers, those with allergies and anyone with a history of respiratory complaints must not be asked to work with products containing isocyanates.

Do not sand, flame cut, braze or weld dry coating without a NIOSH approved air purifying respirator with particulate filters or appropriate ventilation, and gloves.

Revised: July 2018

In the United States and Canada:

1.855.6.AXALTA
metalux.us

