

# Standox® VOC Compliance Chart

Group 1 Vehicles : Cars, large-heavy duty trucks, light/medium duty trucks, vans and motorcycles.

Butte County AQMD Rule 235 - Effective 07/01/1999

Colusa County APCD Rule 2.42 - Effective 07/01/2000

Shasta County AQMD Rule 3:25 - Effective 07/01/1998

Tehama County APCD Rule 4:35 - Effective 07/01/1999



Description	Article #	Compliant Rules				Applied VOC g/L	Remarks
<b>Surface Preparation VOC Limit = 1.67 lbs/gal (200 g/L)</b>							
Standoflex® Low VOC Plastic Cleaner	16010	Butte, Colusa, Shasta, Tehama				21	
Standohyd® Cleaner	16176					188	
Standohyd® VOC Cleaner 25	16178					25	
<b>Surface Preparation (Plastic) VOC Limit = 6.5 lbs/gal (780 g/L) if applied from hand-held spray containers</b>							
Standox® Silicone Remover Antistatic	16203	Butte, Colusa, Shasta, Tehama				773	Must be applied with a spray bottle for compliance.
Description	Article #	Mix Ratio	Hardener	Thinner/Additive	Addtl Product	Max Applied VOC (LE) g/L	Remarks
<b>Pretreatment VOC Limit = 6.5 lbs/gal (780 g/L)</b>							
Standox® 1K Primer Red-Brown (Aerosol)	14696	Ready to Use	N/A	N/A	N/A	N/A	
Standox® 1K Primer	16134	+50%	N/A	2K Thinners	N/A	780	
Standox® Etching Adhesion Primer	16167	1:1	16168	N/A	N/A	780	
Standox® Low VOC Etch Primer	16189	2:1	16190	N/A	N/A	780	
Standox® 1K Primer (Aerosol)	16141/16228	Ready to Use	N/A	N/A	N/A	N/A	
Axalta® Pretreatment Wipes	PS4000™	Ready to Use	N/A	N/A	N/A	780	
<b>Primers/Primer Surfacer VOC Limit = 2.8 lbs/gal (340 g/L)</b>							
Standox® 2.1 Filler	11999	4:1+20-30%	2.1 Hardeners	2.1 Thinners	N/A	340	
Standox® 2.1 Filler w/2K Plasticiser	11999	2:1+30%	2.1 Hardeners	2.1 Thinners	+30% 15260	340	15260 must be added before hardener.
Standox® PF Filler	16220/16221	5:1+10-20%	PF Hardeners	16215, 16224, 16225	N/A	340	
Standox® PF Filler w/2K Plasticiser	16220/16221	5:1 +10-20%	PF Hardeners	16215, 16224, 16225	+15% 15260	340	15260 must be added before hardener.
Standox® 1K Waterborne Primer Surfacers	16231	1 +5-15%	N/A	80188		340	
<b>Primer Sealers VOC Limit = 3.5 lbs/gal (420 g/L)</b>							
Standox® 2.1 Filler	11999	2:1+10-20%	2.1 Hardeners	2.1 Thinners	+30% 16171	420	
Standox® 2.1 Filler w/2K Plasticiser	11999	2:1+10%	2.1 Hardeners	2.1 Thinners	+15% 15260 +30% 16171	420	15260 must be added before hardener.
Standox® PF Sealer	16222/16223	4:1+30%	PF Hardeners	16224, 16225	N/A	420	
Standox® PF Sealer w/2K Plasticiser	16222/16223	4:1+30%	PF Hardeners	16224, 16225	+15% 15260	420	15260 must be added before hardener.
Standox® 2K EP Primer (Aerosol)	16181	Ready to Use	N/A	N/A	N/A	N/A	
<b>Single Stage Topcoats VOC Limit = 5.0 lbs/gal (600 g/L)</b>							
Standocryl® 2K MS	See Price List	2:1+0-10%	2K Hardeners	2K Thinners	N/A	5.0	
Standocryl® 2K MS w/2K Plasticiser	See Price List	2:1+0-10%	2K Hardeners	2K Thinners	+15-30% 15260	5.0	15260 must be added before hardener.
<b>Multistage Topcoat VOC Limit = 5.0 lbs/gal (600 g/L) applied as a 2-stage or 3-stage coating system</b>							
<b>Basecoats: Must be used with specific clearcoats for compliance</b>							
Standox® Basecoat	See Price List	+50%	N/A	MSB Thinners	N/A	600	
Standox® Basecoat	See Price List	+15%+30-40%	2.1 Hardeners	MSB Thinners	N/A	600	Only compliant if used in a 2-stage coating system with 2.1 Clear (10020), 2.1 HS Clear (16156), or 2k HS Clear (14580).
Standox® Basecoat Real Black	14017	+15%+40%	2.1 Hardeners	MSB Thinners	N/A	600	Only compliant if used in a 2-stage coating system with 2.1 Clear (10020), 2.1 HS Clear (16156), or 2k HS Clear (14580).

# Standex® VOC Compliance Chart

Group 1 Vehicles : Cars, large-heavy duty trucks, light/medium duty trucks, vans and motorcycles.

Butte County AQMD Rule 235 - Effective 07/01/1999

Colusa County APCD Rule 2.42 - Effective 07/01/2000

Shasta County AQMD Rule 3:25 - Effective 07/01/1998

Tehama County APCD Rule 4:35 - Effective 07/01/1999



Clearcoats: Must be used as a system with basecoats at/under 5.0 lbs/gal (600 g/L) for compliance							
Standocryl® 2.1 Clear	10020	2:1+5-10%	2.1 Hardeners	2.1 Thinners	N/A	600	
Standocryl® 2.1 Clear w/2K Plasticiser	10020	2:1+5-10%	2.1 Hardeners	2.1 Thinners	+15-30% 15260	600	15260 must be added before hardener.
Standocryl® 2K HS Clear	14580	2:1+0-5%	2.1 Hardeners	2.1 Thinners	N/A	600	Not compliant if used in a 3-stage coating system with Standox Basecoat.
Standocryl® 2K HS Clear w/2K Plasticiser	14580	2:1+0-5%	2.1 Hardeners	2.1 Thinners	+15-30% 15260	600	Not compliant if used in a 3-stage coating system with Standox Basecoat. 15260 must be added before hardener.
Standocryl® 2.1 HS Clear	16156	2:1+5-10%	2.1 Hardeners	2.1 Thinners	N/A	600	
Standocryl® 2.1 HS Clear w/2K Plasticiser	16156	2:1+5-10%	2.1 Hardeners	2.1 Thinners	+15-30% 15260	600	15260 must be added before hardener.
Standocryl® 2.1 HS Clear w/SR Additive	16156	1.5:1+5%	2.1 Hardeners	2.1 Thinners	+ 5% 16207	600	Only compliant if used in a coating system with Standohyd or Standoblu.
Standocryl® VOC Platinum Clear	16161	2:1	2.1 Hardeners	N/A	N/A	600	Not compliant if used in a 3-stage coating system with Standox Basecoat.
Standocryl® Clear PFC 20	16211/ 16217	2:1+15%	PF Hardeners	16215	N/A	600	Not compliant if used with hardened Standox Basecoat.
Standocryl® Clear PFC 20 w/2K Plasticiser	16211/ 16217	2:1+15%	PF Hardeners	16215	+10-15% 15260	600	Not compliant if used with hardened Standox Basecoat. 15260 must be added before hardener.
Standocryl® Clear PFC 30	16216	2:1+5%	PF Hardeners	16215	N/A	600	
Standocryl® Clear PFC 30 w/2K Plasticiser	16216	2:1+10%	PF Hardeners	16215	+10-15% 15260	600	15260 must be added before hardener.
Standocryl® Clear PFC Air Dry	16218	4:1 +20%	PF Hardeners	16215	N/A	600	
Standocryl® Clear PFC Air Dry w/2K Plasticiser	16218	4:1 +20%	PF Hardeners	16215	+10% 15260	600	15260 must be added before hardener.
Standex® 2K Matting Agent Mix 608 w/10020 or 16156 Flat Finish	16199	4:1 w/10020 or 16156	2:1 w/2.1 Hardeners	+5-10% 2.1 Thinners	N/A	600	
Standex® 2K Matting Agent Mix 608 w/10020 or 16156 Satin Finish	16199	3:1 w/10020 or 16156	2:1 w/2.1 Hardeners	+5-10% 2.1 Thinners	N/A	600	
Standex® 2K Matting Agent Mix 608 w/16216 Satin Finish	16199	5:1 w/16216	2:1 w/ 16214	+20% PF Thinner	N/A	600	
Standex® 2K Matting Agent Mix 608 w/16216 Flat Finish	16199	6:1 w/16216	2:1 w/ 16214	+20% PF Thinner	N/A	600	
Specialty Coatings VOC Limit = 7.0 lbs/gal (840 g/L) - Cannot exceed 5% paint volume on a monthly basis.							
Elastomeric Coatings							
Standoflex® Plastic Primer Silver	12065	Ready to Use	N/A	N/A	N/A	840	
Standoflex® Plastic Primer Silver (Aerosol)	14408	Ready to Use	N/A	N/A	N/A	EXEMPT	
Standoflex® 1K Plastic Adhesion Primer	16202/16227	Ready to Use	N/A	N/A	N/A	840	
Standoflex® 2K Plastic Primer Surfacer	11816/16192	1:1	11824	N/A	N/A	840	
Standocryl® 2K Matte Clear 007 (alone or per TDS)	16163	3:1+0-25%	2K Hardeners	2K Thinners	N/A	840	
Standocryl® 2K Rallye Matte Black	10887	3:1+0-10%	2.1 Hardeners	2K Thinners	N/A	840	
Uniform Finish Coatings							
Standex® Basecoat Colorless	16150	Ready to Use	N/A	or +10% MSB Thinners	N/A	840	
Standex® Basecoat Colorless	16150	1:2 w/Standex® Basecoat (RTS)				840	
Standex® Basecoat Colorless	16150	15%	2.1 or 2K Hardeners	N/A	N/A	840	
Standex® 2k Smart Blend Plus	16174	4:1 w/2K Clear (RTS)				840	
Standex® 2k Smart Blend Plus w/2.1 Clear (10020)	16174	See TDS 1206 for compliant mixing recommendations				840	
Standex® 2k Smart Blend Plus w/2.1 HS Clear (16156)	16174	See TDS 1206 for compliant mixing recommendations				840	
Standex® 2k Smart Blend Plus w/PFC 20 (16211)	16174	See TDS 1206 for compliant mixing recommendations				840	
Standex® 2k Smart Blend Plus w/PFC 30 (16216)	16174	See TDS 1206 for compliant mixing recommendations				840	
Standohyd® Special Effect Color Blend	60213	Ready to Use	N/A	N/A	N/A	840	
Standohyd® Special Effect Color Blend	60213	+50%	N/A	60191	N/A	840	
Standohyd® Color Blend	80045	Ready to Use	N/A	N/A	N/A	840	
Standohyd® Color Blend	80045	1:1 w/Standohyd® Basecoat (RTS)				840	
Standoblu® Color Blend	19310/19311	+5-10%	N/A	19301, 19302, 19303	+5% 18316	840	
Standoblu® Color Blend	19310/19311	+0-5%	N/A	18316	N/A	840	
Standex® 2K Fade-Out Thinners 11031	11247	3:1 w/RTS 2K Clear	N/A	N/A	N/A	840	
Other Products							
Standohyd® Sanding Paste	14670	see TDS	N/A	N/A	N/A		

For complete product usage and mixing recommendations, see the product specific technical data sheet located on [www.standexna.com](http://www.standexna.com).

Copyright © 2018 Axalta Coating Systems. Standox® and all products designated with TM or ® are trademarks or registered trademarks of Axalta Coating Systems for its brands of refinish systems. All rights reserved.