

# Standex® VOC Compliance Chart



Antelope Valley Rules 1151/1171 - Effective 05/01/2013  
 Bay Area AQMD Rule 8-45 - Effective 10/01/2009  
 Feather River AQMD Rules 3.14/3.19 - Effective 08/01/2017  
 Imperial County APCD Rule 427 - Effective 04/01/2010  
 Kern County APCD Rule 410-A4 - Effective 03/13/2014  
 Mojave Desert AQMD Regulation XI: Rule 1116 - Effective 07/01/2011  
 Placer County APCD Rule 234 - Effective 07/01/2011  
 Sacramento Metropolitan AQMD Rule 459 - Effective 02/25/2012

San Diego County APCD Rule 67.20.1 - Effective 06/30/2010  
 San Joaquin Valley APCD Rule 4612 - Effective 10/21/2010  
 San Luis Obispo County APCD Rule 423 - Effective 07/01/2010  
 Santa Barbara County APCD Rule 339 - Effective 01/01/2010  
 South Coast AQMD Rules 1151/1171 - Effective 07/01/2008  
 Ventura County APCD Rules 74.6/74.18 - Effective 01/01/2009  
 Yolo-Solano AQMD Rules 2.26/2.31 - Effective 07/01/2010

Description	Article #	Compliant Rules				Applied VOC g/L	Remarks
<b>Surface Preparation VOC Limit = 0.2 lbs/gal (25 g/L)</b>							
Standoflex® Low VOC Plastic Cleaner	16010	Antelope Valley, Bay Area, Feather River, Imperial, Kern, Mojave Desert, Placer, Sacramento Metro, San Diego,				21	
Standohyd® VOC Cleaner 25	16178	San Joaquin Valley, San Luis Obispo, Santa Barbara, South Coast, Ventura, Yolo-Solano				25	
<b>Aerosol Cleaners VOC Limit = EXEMPT</b>							
Standohyd® Cleaner (Aerosol)	16166	Antelope Valley, Feather River, South Coast, Ventura, Yolo-Solano				EXEMPT	Use of up to 160 ounces of non-refillable aerosol containers per day, per facility.
Standox® Silicone Cleaner (Aerosol)	16208					EXEMPT	
<b>Surface Preparation (Other) VOC Limit = 6.5 lbs/gal (780 g/L) if applied from hand-held spray containers</b>							
Standohyd® Cleaner	16176	Kern, San Diego, San Luis Obispo, Santa Barbara, Ventura				188	For wax, grease and other contaminant removal, prior to sanding, must be from a non-aerosol, hand-held spray bottle and is limited to 20 gallons per year, per facility.
Standox® Silicone Remover Antistatic	16203					773	
Description	Article #	Mix Ratio	Hardener	Thinner/ Additive	Addl Product	Max Applied VOC (LE) g/L	Remarks
<b>Pretreatment VOC Limit = 5.5 lbs/gal (660 g/L)</b>							
Standox® Low VOC Etch Primer	16189	2:1	16190	N/A	N/A	660	
Standox® 1K Primer Red-Brown (Aerosol)	14696	Ready to Use	N/A	N/A	N/A	EXEMPT	
Standox® 1K Primer (Aerosol)	16141/16228	Ready to Use	N/A	N/A	N/A	EXEMPT	
Axalta® Pretreatment Wipes	PS4000™	Ready to Use	N/A	N/A	N/A	660	
<b>Primer VOC Limit = 2.1 lbs/gal (250 g/L)</b>							
Standox® 2.1 Filler	11999	4:1+20-30%	2.1 Hardeners	2.1 Thinners	N/A	250	
Standox® 2.1 Filler w/2K Plasticiser	11999	2:1+30%	2.1 Hardeners	2.1 Thinners	+30% 15260	250	15260 must be added before hardener.
Standox® PF Filler	16220/16221	5:1+10-20%	PF Hardeners	16215, 16224, 16225	N/A	250	
Standox® PF Filler w/2K Plasticiser	16220/16221	5:1+10-20%	PF Hardeners	16215, 16224, 16225	+15% 15260	250	15260 must be added before hardener.
Standox® 1K Waterborne Primer Surfacer	16231	1+5-15%	N/A	80188		250	
<b>Primer-Sealer VOC Limit = 2.1 lbs/gal (250 g/L)</b>							
Standox® 2.1 Filler	11999	2:1+10-20%	2.1 Hardeners	2.1 Thinners	+30% 16171	250	
Standox® 2.1 Filler w/2K Plasticiser	11999	2:1+10%	2.1 Hardeners	2.1 Thinners	+15% 15260 +30% 16171	250	15260 must be added before hardener.
Standox® PF Sealer	16222/16223	4:1+30%	PF Hardeners	16224, 16225	N/A	250	
Standox® PF Sealer w/2K Plasticiser	16222/16223	4:1+30%	PF Hardeners	16224, 16225	+15% 15260	250	15260 must be added before hardener.
Standox® 2K EP Primer (Aerosol)	16181	Ready to Use	N/A	N/A	N/A	EXEMPT	
<b>Color Coating VOC Limit = 3.5 lbs/gal (420 g/L)</b>							
Standoblu® Basecoat	See Price List	10-30%	N/A	19301, 19302, 19303	N/A	420	
Standoblu® Basecoat	See Price List	+0-10% +10-30%	17400	19301, 19302, 19303	N/A	420	
Standohyd® Basecoat	See Price List	+10-20%	N/A	80184, 80188	N/A	420	
Standohyd® Basecoat	See Price List	+5% +10-20%	16197	80184, 80188	N/A	420	
Standohyd® Basecoat	See Price List	+ 5-10%	N/A	16191	N/A	420	
<b>Clear Coating VOC Limit = 2.1 lbs/gal (250 g/L)</b>							
Standocryl® 2.1 Clear	10020	2:1+5-10%	2.1 Hardeners	2.1 Thinners	N/A	250	
Standocryl® 2.1 Clear w/2K Plasticiser	10020	2:1+5-10%	2.1 Hardeners	2.1 Thinners	+15-30% 15260	250	15260 must be added before hardener.
Standocryl® 2.1 HS Clear	16156	2:1+5-10%	2.1 Hardeners	2.1 Thinners	N/A	250	
Standocryl® 2.1 HS Clear w/2K Plasticiser	16156	2:1+5-10%	2.1 Hardeners	2.1 Thinners	+15-30% 15260	250	15260 must be added before hardener.
Standocryl® 2.1 HS Clear w/SR Additive	16156	1.5:1+5%	2.1 Hardeners	2.1 Thinners	+5 16207	250	
Standox® 2K Matting Agent Mix 608 w/10020 or 16156 Satin Finish	16199	3:1 w/10020 or 16156	2:1 w/2.1 Hardeners	+5-10% 2.1 Thinners	N/A	250	
Standocryl® Clear PFC 20	16211/ 16217	2:1+15%	PF Hardeners	16215	N/A	250	
Standocryl® Clear PFC 20 w/2K Plasticiser	16211/ 16217	2:1+15%	PF Hardeners	16215	+10-15% 15260	250	15260 must be added before hardener.
Standocryl® Clear PFC 30	16216	2:1+5%	PF Hardeners	16215	N/A	250	
Standocryl® Clear PFC 30 w/2K Plasticiser	16216	2:1+10%	PF Hardeners	16215	+10-15% 15260	250	15260 must be added before hardener.
Standocryl® Clear PFC Air Dry	16218	4:1 +20%	PF Hardeners	16215	N/A	250	
Standocryl® Clear PFC Air Dry w/2K Plasticiser	16218	4:1 +20%	PF Hardeners	16215	+10% 15260	250	15260 must be added before hardener.
Standox® 2K Matting Agent Mix 608 w/10020 or 16156 Flat Finish	16199	4:1 w/10020 or 16156	2:1 w/2.1 Hardeners	+5-10% 2.1 Thinners	N/A	250	
Standox® 2K Matting Agent Mix 608 w/16216 Satin Finish	16199	5:1 w/16216	2:1 w/ 16214	+20% PF Thinner	N/A	250	
Standox® 2K Matting Agent Mix 608 w/16216 Flat Finish	16199	6:1 w/16216	2:1 w/ 16214	+20% PF Thinner	N/A	250	
<b>Uniform Finish Coating VOC Limit = 4.5 lbs/gal (540 g/L)</b>							
Standohyd® Special Effect Color Blend	60213	Ready to Use	N/A	N/A	N/A	540	
Standohyd® Special Effect Color Blend	60213	+50%	N/A	60191	N/A	540	
Standohyd® Color Blend	80045	Ready to Use	N/A	N/A	N/A	540	
Standohyd® Color Blend	80045	1:1 w/Standohyd® Basecoat (RTS)				540	
Standoblu® Color Blend	19310/19311	+5-10%	N/A	19301, 19302, 19303	+5% 18316	540	
Standoblu® Color Blend	19310/19311	+0-5%	N/A	18316	N/A	540	
Standox® 2k Smart Blend Plus w/2.1 Clear (10020)	16174	See TDS 1206 for compliant mixing recommendations					540
Standox® 2k Smart Blend Plus w/2.1 HS Clear (16156)	16174	See TDS 1206 for compliant mixing recommendations					540
Standox® 2k Smart Blend Plus w/PFC 20 (16211)	16174	See TDS 1206 for compliant mixing recommendations					540
Standox® 2k Smart Blend Plus w/PFC 30 (16216)	16174	See TDS 1206 for compliant mixing recommendations					540
<b>Adhesion Promoter VOC Limit = 4.5 lbs/gal (540 g/L)</b>							
Standoflex® Plastic Primer Silver (Aerosol)	14408	Ready to Use	N/A	N/A	N/A	EXEMPT	
Standoflex® 1K Plastic Adhesion Primer	16202/16227	Ready to Use	N/A	N/A	N/A	540	
<b>Other Products</b>							
Standohyd® Sanding Paste	14670	see TDS	N/A	N/A	N/A		